

PRODUCT TYPE	XPON ONT	MODEL: MP-G100Z		
HARDWARE	Chipset	CPU	RTL9601D	
	Interfaces	LAN port	1 * GE port	
	XPON	Standard	GPON: ITU-T G.984/G.988 EPON: IEEE 802.3ah, YD/T 1475-2006	
		Wavelength	1310nm/1490nm	
		Speed	GPON: Upstream 1.244 Gbit/s, downstream 2.488 Gbit/s	
			EPON: Upstream 1.25 Gbit/s, downstream 1.25 Gbit/s	
		Sensitivity	≤-28dBm	
		Emission Power	1dBm≤P≤4dBm	
		Distance	20 km	
		Connector	SC/UPC or SC/APC	
SOFTWARE	Support	Protocols	ITU-T G.984/G.988 IEEE 802.1D, Spanning Tree IEEE 802.1Q, VLAN IGMP v1/v2/v3 IEEE 802.1w, RSTP ITU-T Y.1291	
		Access Mode	Optional : PPPoE, Bridge, IPOE	
		Management	OMCI, TR-069(FreeAcs、 GenieAcs)	
	Security	Algorithm	SP/WRR/SP+WRR	
		Encryption	AES128	
		Authentication	CHAP, PAP	
		Others	Loopback	
OTHERS	Accessories	1 * Power Adaptor		
		1 * Manual		
	Device Parameter	Power Supply	Input 110-240VAC; Output 12V DC/1A	
		Power Consumption	<12W	
		Net Weight	52g	
Size	74mm(L) ×74mm(W) ×20mm(H)			
IMAGE				