

Extended Battery Module

192V / 7.0Ah | 192V / 9.0Ah



Battery Pack



Front Panel



Rear Panel

SPECIFICATIONS

| Model | MR-PBC192-7 | MR-PBC192-9 |
|-----------------------------|--|--------------|
| Compatible model | MR-US6K-H, MR-US6KA-H, MR-US6KRT-H, MR-US6KART-H MR-US10K-H, MR-US10KA-H, MR-US10KRT-H, MR-US10KART-H | |
| GENERAL | | |
| Voltage / Capacity | 192V / 7.0Ah | 192V / 9.0Ah |
| BATTERY | | |
| Battery Size | 12V / 7.0Ah | 12V / 9.0Ah |
| Battery Quantity | 16 PCS | |
| Battery Type | Sealed Lead-Acid | |
| Battery Pack | 16S | |
| Design Floating Life | 3 – 5 years | |
| Self Discharge | 2% of capacity declined per month at (25°C) | |
| PHYSICAL | | |
| Dimensions (D*W*H, mm) | 690 × 438 × 88 | |
| Net Weight (kg) | 46.0 | 51.0 |
| ENVIRONMENTAL | | |
| Operating Relative Humidity | 0% – 90 % (non-condensing) | |
| Operating Temperature | 0°C – 40°C | |
| Operating Altitude | 0 – 10,000ft | |
| Storage Relative Humidity | 0% – 95 % (non-condensing) | |
| Storage Temperature | -20°C – 40°C | |
| Storage Altitude | 0 – 50,000ft | |

Specifications are subject to change without notice, and all product drawings are for reference only. Consult MARSRIVA for the latest design and specifications.